

Product Info

Movie 85 CX

Technical Data

- Type - Home-Cinema-System with active subwoofer system
- Engineering Principle - Front: 2-way closed system
Center: 2-way closed system
Surround: 2-way closed system
Subwoofer: Bandpass system
- Systempower - 100 watts
- Frequency response - Front: 120...25.000 Hz
Center: 120...25.000 Hz
Surround: 120...25.000 Hz
Subwoofer: 38...140 Hz
- Crossover frequency - Front: 5.000 Hz
Center: 5.000 Hz
Surround: 5.000 Hz
Subwoofer: 80...140 Hz (adjustable)
- Woofer - Front: 1 x 80 mm (3"), Aluminum finish
Center: 2 x 80 mm (3"), Aluminum finish
Surround: 1 x 80 mm (3"), Aluminum finish
Subwoofer: 1 x 165 mm (6"), Aluminum finish
- Tweeter - Front: 1 x 15 mm (1"), aluminum
Center: 15 mm (1"), aluminum
Surround: 15 mm (1"), aluminum
- Nominal Impedance - 4...8 ohms
- Dimensions (WxHxD) - Front: 9 x 9 x 10 cm - (3.5" x 3.5" x 3.9")
Center: 19.5 x 9 x 10 cm - (7.7" x 3.5" x 3.9")
Surround: 9 x 9 x 10 cm - (3.5" x 3.5" x 3.9")
Subwoofer: 23 x 36 x 42 cm - (9.1" x 14.2" x 16.5")
- Weight - Front: 0.8 kg
Center: 1.5 kg
Surround: 0.8 kg
Subwoofer: 10.3 kg
- Special Features - Front:
Coax system, Magnetically shielded, Wall brackets included
Center:
Magnetically shielded, Wall brackets included
Surround:
Coax system, Magnetically shielded, Wall brackets included
Subwoofer:
Adjustable crossover frequency, Adjustable bass level, SC-technology

