

Product Info

Movie CD 1000.2

Technical Data

- Type - Home-Cinema-System with active subwoofer system
- Engineering Principle - Front: 2½-way Bass reflex system
Center: 2-way closed system
Surround: 2-way closed system
Subwoofer: Bandpass system
- Nom. /Music power handling - Front: 70 / 120 watts
Center: 45 / 100 watts
Surround: 45 / 100 watts
- Musical output - Subwoofer: 100 watts
- Frequency response - Front: 50...25.000 Hz
Center: 80...25.000 Hz
Surround: 80...25.000 Hz
Subwoofer: 33...140 Hz
- Crossover frequency - Front: 400 / 3.500 Hz
Center: 3.900 Hz
Surround: 3.900 Hz
Subwoofer: 80...140 Hz (adjustable)
- Woofers - Front: 2 x 80 mm (3"), aluminum
Center: 2 x 80 mm (3"), aluminum
Surround: 1 x 80 mm (3"), aluminum
Subwoofer: 1 x 200 mm (8"), Cellulose/graphite
- Midrange - Front: 2 x 80 mm (3"), aluminum
- Tweeter - Front: 1 x 15 mm (1"), aluminum
Center: 1 x 15 mm (1"), aluminum
Surround: 1 x 15 mm (1"), aluminum
- Nominal Impedance - 4...8 ohms
- Dimensions (WxHxD) - Front: 9 x 103 x 10 cm - (3.5" x 40.6" x 3.9")
Center: 22 x 9 x 10 cm - (8.7" x 3.5" x 3.9")
Surround: 9 x 13.5 x 10 cm - (3.5" x 5.3" x 3.9")
Subwoofer: 24 x 42.5 x 42 cm - (9.4" x 16.7" x 16.5")
- Weight - Front: 8.6 kg
Center: 1.7 kg
Surround: 1.0 kg
Subwoofer: 10.4 kg
- Special Features - Front:
Magnetically shielded, Polymer protection, Aluminum speaker base plate
Center:
Magnetically shielded
Surround:
Magnetically shielded, Polymer protection, Wall brackets included
Subwoofer:
Adjustable crossover frequency, Adjustable bass level, SC-technology



Awards:



CANTON[®]
German loudspeaker tradition