

Product Info

Movie CD 1500.2

Technical Data

Type	- Home-Cinema-System with active subwoofer system
Engineering Principle	- Front: 2½-way Bass reflex system Center: 2½-way closed system Surround: 2-way closed system Subwoofer: closed system
Nom. /Music power handling	- Front: 80 / 140 watts Center: 60 / 100 watts Surround: 45 / 100 watts
Musical output	- Subwoofer: 250 watts
Frequency response	- Front: 45...25.000 Hz Center: 50...25.000 Hz Surround: 60...25.000 Hz Subwoofer: 25...200 Hz
Crossover frequency	- Front: 400 / 3.500 Hz Center: 400 / 3.500 Hz Surround: 3.900 Hz Subwoofer: 55...200 Hz (adjustable)
Woofers	- Front: 2 x 80 mm (3"), aluminum Center: 2 x 80 mm (3"), aluminum Surround: 1 x 80 mm (3"), aluminum Subwoofer: 1 x 220 mm (9"), Cellulose/graphite
Midrange	- Front: 2 x 80 mm (3"), aluminum Center: 2 x 80 mm (3"), aluminum
Tweeter	- Front: 1 x Front: 15 mm (1"), aluminum Center: 1 x Center: 15 mm (1"), aluminum Surround: 1 x Surround: 15 mm (1"), aluminum
Nominal Impedance	- 4...8 ohms
Dimensions (WxHxD)	- Front: 9 x 103 x 9 cm - (3.5" x 40.6" x 3.5") Center: 43 x 9 x 9 cm - (16.9" x 3.5" x 3.5") Surround: 9 x 14 x 9 cm - (3.5" x 5.5" x 3.5") Subwoofer: 27 x 33.5 x 29 cm - (10.6" x 13.2" x 11.4")
Weight	- Front: 8.7 kg Center: 3.4 kg Surround: 1.3 kg Subwoofer: 9 kg
Special Features	- Front: Magnetically shielded, Aluminum speaker base plate Center: Magnetically shielded, Wall brackets included Surround: Magnetically shielded, Polymer protection, Wall brackets included Subwoofer: Downfire Woofer, , Adjustable phase limiter, Adjustable crossover frequency, Adjustable bass level, SC-technology

