

Product Info

Movie CD 2000.2

Technical Data

Type	- Home-Cinema-System with active subwoofer system
Engineering Principle	- Front: 2½-way Bass reflex system Center: 2½-way closed system Surround: 2-way closed system Subwoofer: closed system
Nom. /Music power handling	- Front: 90 / 150 watts Center: 70 / 130 watts Surround: 50 / 120 watts
Musical output	- Subwoofer: 250 watts
Frequency response	- Front: 40...30.000 Hz Center: 45...30.000 Hz Surround: 45...30.000 Hz Subwoofer: 30...200 Hz
Crossover frequency	- Front: 400 / 3.300 Hz Center: 400 / 3.500 Hz Surround: 3.900 Hz Subwoofer: 55...200 Hz (adjustable)
Woofers	- Front: 2 x 110 mm (4"), aluminum Center: 1 x 110 mm (4"), aluminum Surround: 1 x 110 mm (4"), aluminum Subwoofer: 1 x 220 mm (9"), Cellulose/graphite
Midrange	- Front: 2 x 110 mm (4"), aluminum Center: 1 x 110 mm (4"), aluminum
Tweeter	- Front: 1 x Front: 25 mm (1"), aluminum Center: 1 x Center: 25 mm (1"), aluminum Surround: 1 x Surround: 25 mm (1"), aluminum
Nominal Impedance	- 4...8 ohms
Dimensions (WxHxD)	- Front: 14 x 110 x 10 cm - (5.5" x 43.3" x 3.9") Center: 43 x 14 x 10 cm - (16.9" x 5.5" x 3.9") Surround: 14 x 22 x 10 cm - (5.5" x 8.7" x 3.9") Subwoofer: 27 x 33.5 x 29 cm - (10.6" x 13.2" x 11.4")
Weight	- Front: 9.3 kg Center: 3.5 kg Surround: 2.0 kg Subwoofer: 9 kg
Special Features	- Front: Magnetically shielded, Aluminum speaker base plate Center: Magnetically shielded, Polymer protection, Table top stand included, Wall brackets included Surround: Magnetically shielded, Polymer protection, Wall brackets included Subwoofer: Downfire Woofer, , Adjustable phase limiter, Adjustable crossover frequency, Adjustable bass level, SC-technology

