

Product Info

Movie CD 2000

Technical Data

- Type - Home-Cinema-System with active subwoofer system
- Engineering Principle - Front: 2½-way Bass reflex system
Center: 2-way closed system
Surround: 2-way closed system
Subwoofer: Bass reflex system
- Nom. /Music power handling - Front: 90 / 150 watts
Center: 70 / 130 watts
Surround: 50 / 120 watts
- Musical output - Subwoofer: 150 watts
- Frequency response - Front: 40...30.000 Hz
Center: 45...30.000 Hz
Surround: 45...30.000 Hz
Subwoofer: 25...200 Hz
- Crossover frequency - Front: 400 / 3.300 Hz
Center: 400 / 3.500 Hz
Surround: 3.900 Hz
Subwoofer: 55...200 Hz (adjustable)
- Woofers - Front: 2 x 110 mm (4"), aluminum
Center: 1 x 110 mm (4"), aluminum
Surround: 1 x 110 mm (4"), aluminum
Subwoofer: 1 x 220 mm (9"), aluminum
- Midrange - Front: 2 x 110 mm (4"), aluminum
Center: 1 x 110 mm (4"), aluminum
- Tweeter - Front: 1 x Front: 25 mm (1"), aluminum
Center: 1 x Center: 25 mm (1"), aluminum
Surround: 1 x Surround: 25 mm (1"), aluminum
- Nominal Impedance - 4...8 ohms
- Dimensions (WxHxD) - Front: 14 x 110 x 10 cm - (5.5" x 43.3" x 3.9")
Center: 43 x 14 x 10 cm - (16.9" x 5.5" x 3.9")
Surround: 14 x 22 x 10 cm - (5.5" x 8.7" x 3.9")
Subwoofer: 25.5 x 45 x 37 cm - (10" x 17.7" x 14.6")
- Weight - Front: 9.3 kg
Center: 3.5 kg
Surround: 2.0 kg
Subwoofer: 12.1 kg
- Special Features - Front:
Magnetically shielded, Aluminum speaker base plate
Center:
Magnetically shielded, Polymer protection, Table top stand included, Wall brackets included
Surround:
Magnetically shielded, Polymer protection, Wall brackets included
Subwoofer:
Adjustable phase limiter, Adjustable crossover frequency, Adjustable bass level, SC-technology



Awards:



CANTON[®]
German loudspeaker tradition