

Product Info

Movie CD 202.2

Technical Data

Type	- Home-Cinema-System with active subwoofer system
Engineering Principle	- Front: 2-way closed system Center: 2½-way closed system Surround: 2-way closed system Subwoofer: closed system
Nom. /Music power handling	- Front: 50 / 120 watts Center: 70 / 130 watts Surround: 50 / 120 watts
Musical output	- Subwoofer: 250 watts
Frequency response	- Front: 45...30.000 Hz Center: 45...30.000 Hz Surround: 45...30.000 Hz Subwoofer: 25...200 Hz
Crossover frequency	- Front: 3.900 Hz Center: 400 / 3.500 Hz Surround: 3.900 Hz Subwoofer: 55...200 Hz (adjustable)
Woofers	- Front: 1 x 110 mm (4"), aluminum Center: 1 x 110 mm (4"), aluminum Surround: 1 x 110 mm (4"), aluminum Subwoofer: 1 x 220 mm (9"), Cellulose/graphite
Midrange	- Center: 1 x 110 mm (4"), aluminum
Tweeter	- Front: 1 x 25 mm (1"), aluminum Center: 25 mm (1"), aluminum Surround: 25 mm (1"), aluminum
Nominal Impedance	- 4...8 ohms
Dimensions (WxHxD)	- Front: 14 x 22 x 10 cm - (5.5" x 8.7" x 3.9") Center: 43 x 14 x 10 cm - (16.9" x 5.5" x 3.9") Surround: 14 x 22 x 10 cm - (5.5" x 8.7" x 3.9") Subwoofer: 25.5 x 45 x 37 cm - (10" x 17.7" x 14.6")
Weight	- Front: 2.0 kg Center: 3.5 kg Surround: 2.0 kg Subwoofer: 9 kg
Special Features	- Front: Magnetically shielded, Polymer protection, Wall brackets included Center: Magnetically shielded Surround: Polymer protection, Wall brackets included Subwoofer: Downfire Woofer, , Adjustable phase limiter, Adjustable crossover frequency, Adjustable bass level, SC-technology

