

Product Info

DM 2

Technical Data

- Type - Virtual Surround System
- Engineering Principle - Surround: 2-way closed system
Subwoofer: Bass reflex system
- Nom. /Music power handling - Surround: 45 / 90 watts
- Systempower - 350 watts
- Frequency response - Surround: 150...30.000 Hz
Subwoofer: 25...150 Hz
- Crossover frequency - Surround: 2.200 Hz
Subwoofer: 150 Hz
- Woofers - Subwoofer: 1 x 220 mm (9"),
Midrange - Surround: 1 x 110 mm (4"), aluminum
- Tweeter - Surround: 1 x Surround: 25 mm (1"), aluminum-manganese
- Nominal Impedance - 4...8 ohms
- Dimensions (WxHxD) - Surround: 12 x 12 x 13 cm - (4.7" x 4.7" x 5.1")
Subwoofer: 25.5 x 45 x 37 cm - (10" x 17.7" x 14.6")
- Weight - Surround: 1.3 kg
Subwoofer: 12.5 kg
- Available accessories - Loudspeaker stand LS 80.2
Wall and ceiling brackets Cantomount
- Special Features - Surround:
Table top stand included, Wall brackets included
- Special Features - 350 watt multi-channel amplifier, Simple remote control operation, Sophisticated Plug & Play solution, SC-technology, Integrated FM tuner (RDS), Fully active 2.1 music and home theater system



Awards:



CANTON[®]
German loudspeaker tradition