

Product Info

Movie CD 1500

Technical Data

- Type - Home-Cinema-System with active subwoofer system
- Engineering Principle - Front: 2½-way Bass reflex system
Center: 2½-way closed system
Surround: 2-way closed system
Subwoofer: Bass reflex system
- Nom. /Music power handling - Front: 80 / 140 watts
Center: 60 / 100 watts
Surround: 45 / 100 watts
- Musical output - Subwoofer: 150 watts
- Frequency response - Front: 45...25.000 Hz
Center: 50...25.000 Hz
Surround: 60...25.000 Hz
Subwoofer: 25...200 Hz
- Crossover frequency - Front: 400 / 3.500 Hz
Center: 400 / 3.500 Hz
Surround: 3.900 Hz
Subwoofer: 55...200 Hz (adjustable)
- Woofers - Front: 2 x 80 mm (3"), aluminum
Center: 2 x 80 mm (3"), aluminum
Surround: 1 x 80 mm (3"), aluminum
Subwoofer: 1 x 220 mm (9"), aluminum
- Midrange - Front: 2 x 80 mm (3"), aluminum
Center: 2 x 80 mm (3"), aluminum
- Tweeter - Front: 1 x Front: 15 mm (1"), aluminum
Center: 1 x Center: 15 mm (1"), aluminum
Surround: 1 x Surround: 15 mm (1"), aluminum
- Nominal Impedance - 4...8 ohms
- Dimensions (WxHxD) - Front: 9 x 103 x 9 cm - (3.5" x 40.6" x 3.5")
Center: 43 x 9 x 9 cm - (16.9" x 3.5" x 3.5")
Surround: 9 x 14 x 9 cm - (3.5" x 5.5" x 3.5")
Subwoofer: 25.5 x 45 x 37 cm - (10" x 17.7" x 14.6")
- Weight - Front: 8.7 kg
Center: 3.4 kg
Surround: 1.3 kg
Subwoofer: 12.1 kg
- Special Features - Front:
Magnetically shielded, Aluminum speaker base plate
Center:
Magnetically shielded, Wall brackets included
Surround:
Magnetically shielded, Polymer protection, Wall brackets included
Subwoofer:
Downfire Woofer, Adjustable phase limiter, Adjustable crossover frequency, Adjustable bass level, SC-technology



Awards:

