



DM 55

Type	2.1 Virtual Surround System
Engineering Principle	Bassreflex
Systempower	200 watts
Frequency response	40...23.000 Hz
Crossover frequency	170 / 3.000 Hz
Woofer	2 x 100 mm (4")
Midrange	2 x 50 mm (2")
Tweeter	2 x 19 mm (1"), Fabric
Connection	1 analog Input (chinch) 1 Bluetooth® 3.0 interface (apt-X® codec) 1 digital Input (coaxial) 1 digital Input (optical) 1 Sub Out
Features	bass and treble control Dolby Digital decoder DTS TruSurround™ Remote control HDF cabinet, bears a weight up to 40 kg (high density fiberboard) integrated Subwoofer LED Display LipSync function for exact speech synchronization Virtual surround sound & stereo playback

Special Features

- simple one-cable installation - just one cable to your TV and one cable for power
- IR-learn-function - controllable with TV-remote
- Voice function - better language playing in Stereo & Surround
- Automatic on/off switch with TV
- Hotel Mode - setting of maximum level (hotels / children)
- ECO Mode - selectable power save mode (On/Off)
- Bluetooth Select - automatic selection of bluetooth input
- IR-delete-function - simple deleting of unwanted learnfunctions
- Direct input selection - ideal learnable smart remotes
- Lip-Sync - for exact speech synchronization
- Equalizer - 3 Presets to adjust the acoustics to the setup location
- Easy-Pairing - easiest connection with source device

Warranty	2 years
Dimensions (WxHxD)	54.5 x 6.8 x 30 cm (21.5" x 2.7" x 11.8")
Weight	5.3 kg
Power consumption	0.38 watts
Carton Content	Canton DM 55 Remote control Power cord Optical digital audio cable Coaxial digital audio cable Analogue stereo audio cable Manual