



DM 900

Type	2.1 Virtual Surround System
Engineering Principle	Soundbar: 2-way, closed system Subwoofer: downfire, closed
Systempower	400 watts
Crossover frequency	180 Hz / 3.000 Hz
Woofers	Subwoofer: 1 x 220 mm (9")
Midrange	4 x 50 (2") mm
Tweeter	Front: 2 x 19 mm (1"), fabric
Connection	1 analog Input (chinch) 1 Bluetooth® 3.0 interface (apt-X® codec) 1 digital Input (coaxial) 1 digital Input (optical) 1 Sub Out
Features	bass and treble control Dolby Digital decoder DTS Digital Surround™ Decoding DTS TruSurround™ Remote control LED Display LipSync function for exact speech synchronization Virtual surround sound & stereo playback wireless Subwoofer signal transmission via a robust 5.8 GHz radio link
Special Features	3 presets to adjust the acoustics to the setup location simple one-cable installation - just one cable to your TV and one cable for power wireless music transmission from your smartphone or Tablet-PC in CD-Quality via Bluetooth® Technology controllable with TV-remote slimline soundbar with solid HDF cabinet (high density fiberboard) soundbar with integrated wall mount

Warranty	2 years
Dimensions (WxHxD)	Soundbar: 89 x 6 x 6.5 cm (35" x 2.4" x 2.6") Subwoofer: 27 x 33 x 27 cm (10.6" x 13" x 10.6")
Weight	Soundbar: 2.9 kg Subwoofer: 8.4 kg
Power consumption	Soundbar: 0.39 watts
Carton Content	Canton DM 900 (Soundbar & Subwoofer) Remote control Power cord Optical digital audio cable Coaxial digital audio cable Analogue stereo audio cable Manual