



Movie 1005.2

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way closed system Center: 2-way closed system Surround: 2-way closed system Subwoofer: Bandpass system
Nom. /Music power handling	Front: 45 / 100 watts Center: 50 / 100 watts Surround: 45 / 100 watts
Musical output	Subwoofer: 120 watts
SPL (1 watt/1m)	85 dB
Frequency response	Front: 80...25.000 Hz Center: 60...25.000 Hz Surround: 80...25.000 Hz Subwoofer: 33...140 Hz
Crossover frequency	Front: 3.900 Hz Center: 3.900 Hz Surround: 3.900 Hz Subwoofer: 80...140 Hz (adjustable)
Woofers	Front: 1 x 80 mm (3.2"), aluminum Center: 2 x 80 mm (3.2"), aluminum Surround: 1 x 80 mm (3.2"), aluminum Subwoofer: 1 x 200 mm (8"), aluminium
Tweeter	Front: 1 x 15 mm (1), Aluminium Center: 1 x 15 mm (1), Aluminium Surround: 1 x 15 mm (1"), Aluminium
Nominal Impedance	4...8 ohms

Special Features	<p>Front: Magnetically shielded Polymer protection Wall brackets included</p> <p>Center: Magnetically shielded</p> <p>Surround: Magnetically shielded Polymer protection Wall brackets included</p> <p>Subwoofer: Adjustable crossover frequency Adjustable bass level SC-technology</p> <p>5 years warranty for front-,center- and rear- speaker 2 years warranty for subwoofer</p>
Dimensions (WxHxD)	<p>Front: 9 x 13.8 x 10 cm (3.5 x 5.4 x 3.9) Center: 22 x 9 x 10 cm (8.7 x 3.5 x 3.9) Surround: 9 x 13.8 x 10 cm (3.5 x 5.4 x 3.9) Subwoofer: 24 x 41 x 42 cm (9.5 x 15.9 x 16.5)</p>
Weight	<p>Front: 0.8 kg Center: 1.2 kg Surround: 0.8 kg Subwoofer: 9.8 kg</p>
Power consumption	0,42 Watt
Available accessories	Loudspeaker stand LS 90.2
Carton Content	<p>Canton Movie 1005.2 Wallmounts Equipment feet Manual</p>