



Movie 1505

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way closed system Center: 2½-way closed system Surround: 2-way closed system Subwoofer: Bandpass system
Nom. /Music power handling	Front: 45 / 100 watts Center: 60 / 150 watts Surround: 45 / 100 watts
Nenn- / Musikleistung	Subwoofer: 200 / 250 watts
Frequency response	Front: 60...25.000 Hz Center: 50...25.000 Hz Surround: 60...25.000 Hz Subwoofer: 30...200 Hz (adjustable)
Crossover frequency	Front: 3.900 Hz Center: 400 / 3.500 Hz Surround: 3.900 Hz Subwoofer: 55...200 Hz (adjustable)
Woofers	Front: 1 x 80 mm (3"), aluminum Center: 2 x 80 mm (3"), aluminum Surround: 1 x 80 mm (3"), aluminum Subwoofer: 1 x 220 mm (9"), Cellulose/graphite
Tweeter	Front: 1 x 15 mm, Aluminium Center: 1 x 15 mm, Aluminium Surround: 1 x 15 mm (1"), Aluminium
Nominal Impedance	4...8 ohms
Special Features	Front: Polymer protection Center: Wall brackets included Surround: Polymer protection Wall brackets included Subwoofer: Downfire Woofer Adjustable phase limiter Adjustable crossover frequency
Dimensions (WxHxD)	Front: 9 x 14 x 9 cm (3.5" x 5.5" x 3.5") Center: 43 x 9 x 9 cm (16.9" x 3.5" x 3.5") Surround: 9 x 14 x 9 cm (3.5" x 5.5" x 3.5") Subwoofer: 27 x 33.5 x 29 cm (10.6" x 13.2" x 11.4")
Weight	Front: 1.0 kg Center: 3.4 kg Surround: 1.0 kg Subwoofer: 9 kg
Power consumption	0,32 Watt

Carton Content

Canton Movie 1505
Wallmounts
Equipment feet
Manual