

CANTON

Movie 1550



€2,349.00 *
inkl. MwSt.



Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2½-way bass reflex system Center: 2½-way closed Surround: 2-way closed Subwoofer: closed
Nom. /Music power handling	Front: 80 / 140 watts Center: 60 / 150 watts Surround: 45 / 100 watts
Nenn- / Musikleistung	Subwoofer: 200 / 250 watts
Frequency response	Front: 45...25.000 Hz Center: 50...25.000 Hz Surround: 60...25.000 Hz Subwoofer: 30...200 Hz (adjustable)
Crossover frequency	Front: 400 / 3.500 Hz Center: 400 / 3.500 Hz Surround: 3.900 Hz Subwoofer: 55...200 Hz (adjustable)
Woofers	Front: 2 x 80 mm (3"), aluminum Center: 2 x 80 mm (3"), aluminum Surround: 1 x 80 mm (3"), aluminum Subwoofer: 1 x 220 mm (9"), Cellulose/graphite
Tweeter	Front: 1 x 15 mm, Aluminium Center: 1 x 15 mm, Aluminium Surround: 1 x 15 mm (1"), Aluminium
Special Features	Front: Aluminum speaker base plate Center: Wall brackets included Surround: Polymer protection Wall brackets included Subwoofer: Downfire Woofer Adjustable phase limiter Adjustable crossover frequency Adjustable bass level SC-technology
Nominal Impedance	4...8 ohms



Front: 9 x 103 x 9 cm
(3.5" x 40.6" x 3.5")

Center: 43 x 9 x 9 cm
(16.9" x 3.5" x 3.5")

Surround: 9 x 14 x 9 cm
(3.5" x 5.5" x 3.5")

Subwoofer: 27 x 33.5 x 29 cm
(10.6" x 13.2" x 11.4")

Dimensions (WxHxD)

Weight

Front: 8.7 kg
Center: 3.4 kg
Surround: 1.0 kg
Subwoofer: 9 kg

Power consumption

0,32 Watt

Carton Content

Canton Movie 1550
Wallmounts
Equipment feet
Screw driver
Manual