



## Movie 2050.3

Type	Home-Cinema-System with active subwoofer system
Engineering Principle	Front: 2-way Bassreflexsystem Center: 2-way closed system Surround: 2-way closed system Subwoofer: closed
Nom. /Music power handling	Front: 90 / 150 watts Center: 70 / 130 watts Surround: 50 / 120 watts
Nenn- / Musikleistung	Subwoofer: 200 / 250 watts
Frequency response	Front: 40...30.000 Hz Center: 45...30.000 Hz Surround: 45...30.000 Hz Subwoofer: 30...200 Hz (adjustable)
Crossover frequency	Front: 400 / 3.300 Hz Center: 400 / 3.500 Hz Surround: 3.900 Hz Subwoofer: 55...200 Hz (adjustable)
Woofer	Front: 2 x 110 mm (4"), aluminum Center: 1 x 110 mm (4"), aluminum Surround: 1 x 110 mm (4"), aluminum Subwoofer: 1 x 220 mm (9"), Cellulose/graphite
Tweeter	Front: 1 x 25 mm, Aluminium Center: 1 x 25 mm, Aluminium Surround: 1 x 25 mm (1"), Aluminium
Nominal Impedance	4...8 ohms

Special Features	<p>Front: Magnetically shielded Aluminum speaker base plate</p> <p>Center: Magnetically shielded Polymer protection Table top stand included Wall brackets included</p> <p>Surround: Magnetically shielded Polymer protection Wall brackets included</p> <p>Subwoofer: Downfire Woofer Adjustable phase limiter Adjustable crossover frequency Adjustable bass level</p> <p>5 years warranty for front-,center- and rear- speaker 2 years warranty for subwoofer</p>
Dimensions (WxHxD)	<p>Front: 14.5 x 105 x 10.5 cm Center: 40 x 14.5 x 10.5 cm Surround: 14.5 x 21.4 x 10.5 cm Subwoofer: 27 x 33.3 x 29.5 cm</p>
Weight	<p>Front: 9.3 kg Center: 3.5 kg Surround: 2.0 kg Subwoofer: 9 kg</p>
Power consumption	0,32 Watt
Available accessories	Loudspeaker stand LS 250.2
Carton Content	<p>Canton Movie 2050.2 Wallmounts Speaker stand Center Equipment feet Manual</p>