



DM 5

Type	2.1 Virtual Surround System
Engineering Principle	Broadband bass reflex system with passive membrane
Systempower	120 watts
Frequency response	40...23.000 Hz
Woofer	2 x 99 mm x 56 mm, metal, wavesurround (passive) 2 x 3.9" x 2.2", metal, wavesurround (passive)
Midrange	4 x 51 mm (cellulose graphit), Broadband chassis 4 x 2" (cellulose graphit)
Connection	1 analog Input (cinch) 1 Bluetooth® 3.0 interface (apt-X® codec) 1 digital Input (coaxial) 1 digital Input (optical) 1 Sub Out
Features	bass and treble control Dolby Digital decoder DTS TruSurround™ Remote control HDF cabinet, bears a weight up to 40 kg (high density fiberboard) integrated Subwoofer LED Display LipSync function for exact speech synchronization Virtual surround sound & stereo playback

Special Features

- simple one-cable installation - just one cable to your TV and one cable for power
- IR-learn-function - controllable with TV-remote
- Voice function - better language playing in Stereo & Surround
- Automatic on/off switch with TV
- Hotel Mode - setting of maximum level (hotels / children)
- ECO Mode - selectable power save mode (On/Off)
- Bluetooth Select - automatic selection of bluetooth input
- IR-delete-function - simple deleting of unwanted learnfunctions
- Direct input selection - ideal learnable smart remotes
- Lip-Sync - for exact speech synchronization
- Equalizer - 3 Presets to adjust the acoustics to the setup location
- Easy-Pairing - easiest connection with source device

Warranty	2 years
Dimensions (WxHxD)	55 x 6,4 x 9 cm (21.7" x 2.5" x 3.5")
Weight	3.0 kg
Power consumption	0.38 watts
Carton Content	Canton DM 5 Remote control Power cord Optical digital audio cable Coaxial digital audio cable Analogue stereo audio cable Manual