



DM 60

Type	2.1 Virtual Surround System
Engineering Principle	Bassreflex
Systempower	200 watts
Frequency response	40...23.000 Hz
Crossover frequency	170 / 3.000 Hz
Woofer	2 x 100 mm (4")
Midrange	2 x 50 mm (2")
Tweeter	2 x 19 mm (1"), Fabric
Connection	1 analog Input (chinch) 1 Bluetooth® 3.0 interface (apt-X® codec) 1 digital Input (coaxial) 1 digital Input (optical) 1 Sub Out
Features	bass, mid and treble control (+/-6 dB) Dolby Digital decoder DTS TruSurround™ Remote control HDF cabinet, bears a weight up to 40 kg (high density fiberboard) integrated Subwoofer LED Display LipSync function for exact speech synchronization Virtual surround sound, stereo playback and music surround sound Sleep timer Automatic bluetooth playback Reset - factory settings Input configuration - input renaming

Special Features

- simple one-cable installation - just one cable to your TV and one cable for power
- IR-learn-function - controllable with TV-remote
- Voice function - better language playing in Stereo & Surround
- Automatic on/off switch with TV
- Hotel Mode - setting of maximum level (hotels / children)
- ECO Mode - selectable power save mode (On/Off)
- Bluetooth Select - automatic selection of bluetooth input
- IR-delete-function - simple deleting of unwanted learnfunctions
- Direct input selection - ideal learnable smart remotes
- Lip-Sync - for exact speech synchronization
- Equalizer - 3 Presets to adjust the acoustics to the setup location
- Easy-Pairing - easiest connection with source device

Warranty	2 years
Dimensions (WxHxD)	54.5 x 7.1 x 30 cm (21.5" x 2.8" x 11.8")
Weight	5.3 kg
Power consumption	0.38 watts
Carton Content	Canton DM 60 Remote control Power cord Optical digital audio cable Coaxial digital audio cable Analogue stereo audio cable Manual